

MINI-MELTER



Activating: First remove the protective cover and press switch to activate the tool. The melting knife heats up very quickly. **RISK OF BURNING!** (Cool down period 1 minute). As soon as the melting knife is heated, the filling material can be liquefied.



Product Features: The heat capacity of the smelter by about half an hour continuous operation is guaranteed. However, it is recommended to work at shorter intervals and the smelter in between off. The hard wax filler is made from high quality raw materials made, has very good adhesion properties and is well loaded.



Exchange of batteries: The Mini-Melter tool is supplied with two AA 1.5V batteries. To replace batteries, use a screwdriver to open the tool casing. When inserting batteries please ensure that they are positioned correctly (see +/- symbols on the batteries and casing).

Specifications: Voltage: 3 V, current: 2.75 ± 0.2 amps, Power: 8W, disposal batteries may not be disposed of with household waste (hazardous waste only).



Cleaning melter: Use the cleaning comb to clean the planer grooves. To clean melting knife, simply wipe with a cloth after use.

Use: the optimal set for the repair of scratches, small holes, dents and edge damage. Can be used on wood, laminate and high quality furniture, as well as stairs, doors and kitchen cabinets. Set in hard wax as a filler (in various wood tones), and necessary tools are included.

Content:
4 x Hard Wax
1 x Mini-Melter incl. 2 x batteries
2 x Sanding Pad, grey

MINI REPAIR KIT

For parquet, laminate, and wood surfaces



picobello® by Heinrich König & Co. KG
Distributed by KONIG NORTH-AMERICA, LLC
2800 Black Lake Place, Unit D PHILADELPHIA, PA 19154
PHONE: 215 - 426 - 6216

Numerous application videos about the picobello® products are available at www.picobello-shop.us or on the picobello YouTube Channel (www.youtube.com/PicobelloUSA), as well. So, just have a look ...

IT'S JUST SO EASY ...



1 Preparing

The area to be repaired has to be clean, dry and free from grease. If necessary, remove any loose or sticking out particles.



2 Color selection

Make sure to use always several colour shades from light to dark.



3 Melting

Hold the button down on the side of the combination tool for 30 seconds and then touch the tip onto the fillers. The filler will then melt onto the tip of the tool. CAUTION - DO NOT TOUCH THE TIP WHEN HOT.



4 Filling

Touch the tip of the applicator onto the damaged area and the filler will run into the affected area. **TIP:** Start with the lighter background colour and gradually apply darker colours to mimic the darker grain shade.



5 Levelling

The filler will cure in approximately 30 seconds. Hold the applicator with the grooves flat to the surface and then move it back and forth over the filler until all surplus filler has been removed.



6 Color Adjustment

For precise adjustment, imitate the grain pattern with a darker hue of filler. Then again, level off excess material with the grooves of the Mini-Melter.



7 Finish

Use the grey sanding pad to decrease the area. At the same time the gloss sheen of the repair is flattened.

